

## **BWT-3000**

BWT-3000 is a high purity solution of morpholine

### **ADVANTAGES:**

**BWT-3000 is an excellent condensate pH control, corrosion protection product where a high neutralizing capacity and medium distribution ratio is required.**

### **PRINCIPLE USES:**

**BWT-3000 is suitable for boiler systems in the 0-2600 psig range. It is intended to control pH depression due to the presence of CO<sub>2</sub>.**

### **PROPERTIES:**

**BWT-3000 is a clear to amber liquid with a distinctive amine odor.**

**pH is 12.0/+/-0.50**

**Specific Gravity is 1.0 @ 85 degrees F.**

**Flash Point > 135 degrees F, closed cup**

### **TREATMENT LEVEL:**

**BWT-3000 feed rates range from 10-1000 ppb depending on system CO<sub>2</sub> levels.**

### **APPLICATION:**

**BWT-3000 should be fed based on FCT recommendations and using FCT recommended feed/storage equipment.**

### **HANDLING and STORAGE:**

**BWT-3000 may cause irritation or burns to eyes and skin. Please refer to the MSDS and Product Label Safety Information for complete handling and safety instructions.**

### **SHIPPING:**

**BWT 3000 is available in 55 gallon, 450 pound drums, IBC Totes, bulk quantities and the FCT trademark "Small Bulk" delivery system.**

The information herein is intended as a selection guide. Specific applications should be thoroughly reviewed with your FCT representative. Products are warranted to be both the generic material and concentration specified. No application or performance warranty is extended or implied herein.