

BWT-3300

BWT-3300 is a high purity solution of DEAE and cyclohexylamine

ADVANTAGES:

BWT-3300 is an excellent condensate pH control, corrosion protection product where the advantages of DEAE and cyclohexylamine are required.

BWT-3300 is custom blended to each application to exactly fit the requirements of complex steam condensate systems.

BWT-3300 products are USDA and FDA approved to levels of 130 ppm in the steam.

PRINCIPLE USES:

BWT-3300 is suitable for boiler systems in the 0-2600 psig range. It is intended to control pH depression due to the presence of CO₂.

PROPERTIES:

BWT-3300 is a clear to amber liquid with a distinctive amine odor.

pH is 12.0/+/-0.50

Specific Gravity is 1.0 @ 85 degrees F.

Flash Point > 135 degrees F, closed cup

TREATMENT LEVEL:

BWT-3300 feed rates range from 10-1000 ppb depending on system CO₂ levels.

APPLICATION:

BWT-3300 should be fed based on FCT recommendations and using FCT recommended feed/storage equipment.

HANDLING and STORAGE:

BWT-3300 may cause irritation or burns to eyes and skin. Please refer to the MSDS and Product Label Safety Information for complete handling and safety instructions.

SHIPPING:

BWT 3300 is available in 55 gallon, 450 pound drums, IBC Totes, bulk quantities and the FCT trademark "Small Bulk" delivery system.

The information herein is intended as a selection guide. Specific applications should be thoroughly reviewed with your FCT representative. Products are warranted to be both the generic material and concentration specified. No application or performance warranty is extended or implied herein.