

## CWT-2500

CWT-2500 are application specific products for extreme conditions where environmental issues, makeup water quality, water re-use, exotic metallurgies, severe corrosion and/or deposition require SOTA attention. The blend of monomers, polymers, co-polymers, ter-polymers and corrosion inhibitors are custom fit to each application after intensive investigation by trained FCT personnel.

### ADVANTAGES:

SOTA targeted programs specific to ALL the technical needs of the application.

### PRINCIPLE USES:

CWT-2500 provides outstanding performance controlling deposition and corrosion while addressing the sometimes overlooked issues of downstream water re-use, unusual system components and metallurgies such as high efficiency tower fills, FDA, EPA and USDA requirements.

### PROPERTIES:

CWT-2500 is a amber to clear liq

pH undiluted is 2.3 to 12.0

Specific Gravity is 1.10 to 1.20

Flash Point – non combustible

### TREATMENT LEVEL:

Typical dosages range from 10 to 100 ppm. Product is application specific and should be used in consultation with your FCT representative.

### APPLICATION:

CWT-2500 should be fed on a continuous basis to control scaling and deposition and corrosion. It is compatible with stainless steel, Teflon, viton, plastics and most materials used for chemical feed systems.

### HANDLING and STORAGE:

CWT-2500 may cause irritation or burns to eyes and skin. Please refer to the MSDS and Product Label Safety Information for complete handling and safety instructions.

### SHIPPING:

CWT-2500 is available in 550 pound drums, 2750 pound IBC totes and bulk quantities. CWT-2500 can also be supplied via our trademark “Small Bulk” Delivery System.

The information herein is intended as a selection guide. Specific applications should be thoroughly reviewed with your FCT representative. Products are warranted to be both the generic material and concentration specified. No application or performance warranty is extended or implied herein.