

CWT-3000

CWT-3000 is recommended for most cooling systems where mild steel corrosion is particularly difficult and where the program must be economical. A polymeric dispersant, copolymer, phosphonate and polyphosphate provide scale control in severe conditions.

ADVANTAGES:

Cost effective deposit and corrosion control designed for mild steel systems.

PRINCIPLE USES:

CWT-3000 provides good deposit control and effective mild steel corrosion protection in a cost effective package. Use in conjunction with other 3000 series products to target general corrosion issues to address special cases such as localized pitting and under-deposit attack.

PROPERTIES:

CWT-3000 is a amber to clear liquid

pH undiluted is 3.0-3.5

Specific Gravity is 1.10 to 1.17

Flash Point – non combustible

TREATMENT LEVEL:

Typical dosages range from 10 to 100 ppm. Product is application specific and should be used in consultation with your **FCT** representative.

APPLICATION:

CWT-3000 should be fed on a continuous basis to control scaling and deposition and corrosion. It is compatible with stainless steel, Teflon, viton, plastics and most materials used for chemical feed systems.

HANDLING and STORAGE:

CWT-3000 may cause irritation or burns to eyes and skin. Please refer to the MSDS and Product Label Safety Information for complete handling and safety instructions.

SHIPPING:

CWT-3000 is available in 530 pound drums, 2650 pound IBC totes and bulk quantities. CWT-3000 can also be supplied via our trademark “Small Bulk” Delivery System.

The information herein is intended as a selection guide. Specific applications should be thoroughly reviewed with your FCT representative. Products are warranted to be both the generic material and concentration specified. No application or performance warranty is extended or implied herein.