

CWT-3500

CWT-3500 is a blend of terpolymer, phosphate and zinc intended to provide a stable product capable of providing outstanding mild steel corrosion protection in severe duty cooling systems.

PRINCIPLE USES:

CWT-3500 is intended to provide mild steel corrosion protection over a broad range of pH and TDS conditions. Fed in conjunction with CWT-3000 or similar primary products to provide complete treatment of severe duty systems.

PROPERTIES:

CWT-3500 is a amber to clear liquid

pH undiluted is 2.0-2.3

Specific Gravity is 1.20-1.24

Flash Point – non combustible

TREATMENT LEVEL:

Typical dosages range from 10 to 100 ppm. Product is application specific and should be used in consultation with your FCT representative.

APPLICATION:

CWT-3500 should be fed on a continuous basis to control scaling and deposition and corrosion. It is compatible with stainless steel, Teflon, viton, plastics and most materials used for chemical feed systems.

HANDLING and STORAGE:

CWT-3500 may cause irritation or burns to eyes and skin. Please refer to the MSDS and Product Label Safety Information for complete handling and safety instructions.

SHIPPING:

CWT-3500 is available in 550 pound drums, 2750 IBC totes and bulk quantities. CWT-3500 can also be supplied via our trademark “Small Bulk” Delivery System.

The information herein is intended as a selection guide. Specific applications should be thoroughly reviewed with your FCT representative. Products are warranted to be both the generic material and concentration specified. No application or performance warranty is extended or implied herein.