

CWT-3900

CWT-3900 is a 70% solution of zinc chloride intended for mild steel corrosion protection in cooling water systems.

PRINCIPLE USES:

CWT-3900 is intended to provide mild steel corrosion protection when fed along with CWT-3000.

PROPERTIES:

CWT-3900 is a pale yellow liquid

pH undiluted is <1.0

Specific Gravity is 1.57-1.98

Flash Point – non combustible

TREATMENT LEVEL:

Typical dosages range from 0.2 to 5.0 ppm. Product is application specific and should be used in consultation with your **FCT** representative.

APPLICATION:

CWT-3900 should be fed on a continuous basis to control scaling and deposition and corrosion. It is compatible with stainless steel, Teflon, viton, plastics and most materials used for chemical feed systems.

HANDLING and STORAGE:

CWT-3900 is highly acidic and will cause burns to eyes and skin. Please refer to the MSDS and Product Label Safety Information for complete handling and safety instructions.

SHIPPING:

CWT-3900 is available in 700 pound drums, 2670 pound IBC totes and bulk quantities. **CWT-3900** can also be supplied via our trademark “Small Bulk” Delivery System.

The information herein is intended as a selection guide. Specific applications should be thoroughly reviewed with your **FCT** representative. Products are warranted to be both the generic material and concentration specified. No application or performance warranty is extended or implied herein.