

CWT-BZT-5100

CWT-BZT-5100 is a concentrated liquid solution of sodium benzotriazole

ADVANTAGES:

Copper and copper alloy corrosion inhibitor with improved performance in the presence of oxidizers such as bleach or chlorine gas.

PRINCIPLE USES:

CWT-BZT-5100 is recommended for corrosion protection of copper and copper alloys in cooling water systems of all types.

PROPERTIES:

CWT-BZT-5100 is a amber to tan liquid

pH 13.5 @ 60 degrees F

Specific Gravity is 1.19 @ 60 degrees F

Flash Point – non combustible

Freeze Point – (25) degrees F

TREATMENT LEVEL:

Typical dosages range for CWT-BZT-5100 is from 0.25 to 5.0 ppm. Use in consultation with your FCT representative.

APPLICATION:

CWT-BZT-5100 can be fed on a continuous basis or can be added on an intermittent or manual basis. It is compatible with stainless steel, Teflon, viton, plastics and most materials used for chemical feed systems.

HANDLING and STORAGE:

CWT-BZT-5100 may cause irritation or burns to eyes and skin. Please refer to the MSDS and Product Label Safety Information for complete handling and safety instructions.

SHIPPING:

CWT-BZT-5100 is available in 530 pound drums, 2750 pound IBC totes and bulk quantities. Product is also available under the FCT trademark “Small Bulk” Delivery System.

The information herein is intended as a selection guide. Specific applications should be thoroughly reviewed with your FCT representative. Products are warranted to be both the generic material and concentration specified. No application or performance warranty is extended or implied herein.