

## *WT-466 Coagulant - Technical Bulletin*

### **DESCRIPTION:**

WT-466 is a concentrated inorganic coagulant suitable for coagulation requirements at all pH levels. Intended for use in combination with a precipitant and an anionic polymer for solid/liquid separation. Will promote liquid clarity, achieve charge neutralization, and assist in sludge conditioning.

### **APPLICATIONS:**

WT-466 is suited for flow-through precipitation, batch treatment, and micro-filtration applications. Not as effective as a blended coagulant when wastestream contains a high level of organics such as cleaners or surfactants.

### **OPERATING PARAMETERS:**

Working Concentration	100 to 500 ppm typically
Solution Make-up	No dilution necessary
PH Range:	6.0 to 11.0
Mixing	Medium-speed

### **PHYSICAL PROPERTIES:**

Appearance	Clear, near-colorless liquid
PH as supplied	4-5
Odor	Odorless
Specific Gravity	1.34
Solubility in water	Complete

### **SAFETY AND STORAGE:**

May cause some eye, skin, or mucous membrane irritation with prolonged direct exposure.

### **MISCELLANEOUS**

Packaging comes in 5-gallon pails and 55-gallon drums. Consult MSDS sheet for additional information.

The information given in this technical data sheet is to the best of our knowledge accurate. It is intended to be helpful but no warranty is expressed or implied regarding the accuracy of such data. It is the users responsibility to determine the suitability of his own use of the product described herein; and since conditions of the use are beyond our control, we disclaim all liability with respect to the use of any material supplied by us. Nothing contained herein shall be construed as permission or as recommendations to practice any patented invention without a license from the patent owner nor as recommendation to use any product or to practice ant patented invention without a license from the patent owner nor as recommendation to use any product or to practice any process in violation of any law or any government regulations. Revised 6.4.02